



INFORMATION & GUIDELINES FOR THE INSTALLATION OF TERRAZZO TILES

RECOMMENDED INSTALLATION

SOLI Terrazzo's unique blend of concrete with natural stone flecks lends itself to a diverse range of surfaces. Large format 19.75"x19.75" tile can be easily applied to any exterior or interior surface.

We always recommend dry-fitting your pattern first to think about your cuts in advance and to make sure you like the pattern. This will also help you choose which pieces go where, which is especially helpful with tiles that have a lot of variation.

SUBSTRATES

All substrates should be firmly fixed, flat, clean, dry and free of contaminants such as dust, oil, paint, sealers etc. to ensure proper adhesion. Painted surfaces must be scuffed or sanded for the product and adhesive to bond correctly. Wet areas need special attention and require appropriate substrates, e.g. concrete, cement boards (compressed sheet), and/or treated plywood. The use of reinforced waterproof membranes is suggested, and in the case of floors, a fall to the drainage point of no less than two inches. The use of metal lathing is recommended for larger heavier stones to ensure maximum support of the structure.

WATERPROOF MEMBRANES

Waterproof membranes prevent leakage of water through to the sub-floor framing and/or habitable spaces below. Particular attention must be paid to carrying the membrane up the wall, outside shower boxes, installation of bond breakers and sealing around penetrations. It is strongly recommended that membrane systems be used in all wet areas. Some systems involve the use of a primer.

CUTTING

All cuts to SOLI Terrazzo tiles can be made with a wet saw using a diamond blade.

ADHESIVE

Follow the adhesive manufacturer's instructions carefully. SOLI does not recommend one brand of adhesive over another. Please check with your local tile supply store for alternative and comparable products.

The manufacturer's literature will explain if the adhesive product is suitable for interiors and/or exteriors, as well as walls and floors. Most thinset mortars (multi purpose and polymer modified thinsets) are adequate for installing terrazzo tile. A cement-based adhesive is



generally suitable on masonry substrates where no movement is anticipated. Where slight movement could occur through thermal or pedestrian loads, a modified cement adhesive should be used as a minimum. A bonding agent is recommended for larger, heavier stones.

It is very important that each stone is embedded in the adhesive. To make sure there is 100% coverage you can tap the stones into the adhesive with a rubber mallet.

GROUTING

If you are doing a butt-joint installation grout may not be necessary. Grout should be designed for external or internal conditions whichever may be the case. If you are leaving a grout joint 1/8" or smaller, non-sanded grout is recommended.

SEALANTS

To prevent possible staining and discoloration we recommend sealing all terrazzo tiles BEFORE installation, and if using grout AFTER the grouting process.

BEFORE applying sealant, wash the tiles and let dry for 24-48 hours. This will ensure that moisture is not present under the surface of the tile. Failure to allow tiles to dry completely before application will result in permanent discolorations. We recommend testing all sealants on a single tile before application. There are various products available on the market, however, we recommend contacting your nearest tile supplier for the most appropriate sealer for your application.

CARE & CLEANING

SOLI Terrazzo tiles must be regularly cleaned and maintained to extend the life and beauty of the tile. The tiles can be cleaned with a neutral mild detergent, or a PH neutral cleaner. Staining may occur if the tile is left unsealed. Consequently, any spills should be cleaned quickly to lessen the degree of the stain. For tiles in high traffic areas, keep surfaces clean from abrasive dirt. Do not use abrasive cleaners, powders, scouring pads, steel wool or sandpaper. Do not let soap, bleach or other cleaning solutions set on the surface.